## Certic APPLICATION FORM Suspended Solids Measurement (Flow-thru)

Customer
City Country
Contact
TelFax
E-mail
Date
Application
Replaces, Type & Brand
Position
Media Pressurebar_ TemperatureºC  ☐ Corrosive ☐ Abrasive ☐ Viscose  ☐ Risk of plugging in sensor or pump
Ability of suitable pump. Should be able to work continuously. Large free passage for solids is recommended. Pump with strainer may plug. Capacity >20liters/minute. (6 gpm)
Measuring Rangemg/l (ppm) Pre calibration
Remarks Signature

## **Comments and FAQ**

Hand rail? Wall? Screws, Bolts and nuts?
Hoses, 25mm inner diameter, inforced PVC, suitable length between pump, CT-sensor and outlet with hose clamps. At pipe connection, type of couplings?
Power supply 115/230/240VAC, 50-60Hz, 25VA. When mounted permanently. Safety switch should be placed near the unit. Power supply to pump (incl. safety switch). Quality of power?
Pressurized air to automatic cleaning >2bar. (Nominal 6bar). 6mm (1/4") pneumatic hose with isolation valve.
Purpose of measuring? Monitoring Control Alarm

## **Trouble shooting:**

•	How performs the meter and when did it occur the first time?
•	Has the meter been switched off or has it been power supply cut off? Has the position of the unit been changed? Changes in the process?
•	When was the unit calibrated last time? By whom?
•	Is the customer familiar with the CSP-menus and how to use them? Is it possible to interpret the information in the system window?
•	What are the readings in the system window?
•	Has "total reset" been performed? If so, was there any change in the meter performance?
•	Is there still a flow through the sensor? Has the pump been checked?
•	Is the automatic cleaning working? Has the brush been checked?
•	Other notes